

First Strike™ Low-Temp AFFF Solution (US-FS-LT)

Technical Data Sheet

US Foam Technologies, Inc.

DESCRIPTION

First Strike™ Low-Temp AFFF (Aqueous Film-Forming Foam) Solution is a premixed, synthetic firefighting foam solution designed for use on non-polar, hydrocarbon hazards. It provides excellent control and extinguishment of Class B fires by spreading a vapor-sealing film over the liquid fuel. This vapor seal inhibits reflash even when the foam blanket is ruptured, and also allows the product to be used to secure non-ignited spills.

First Strike™ Low-Temp AFFF Solution also provides excellent penetrating and wetting qualities when used on Class A fires. This is important when extinguishing deep-seated fires in wood, paper, rubber tires and ordinary combustibles.

RECOMMENDED APPLICATION

First Strike™ Low-Temp AFFF Solution is premixed with water and is ready to use from the container. **IMPORTANT: DO NOT PROPORTION OR DILUTE.** It is intended for use on Class B hydrocarbon fuels such as gasoline, diesel fuels, fuel oils, etc. It is not suitable for use on polar solvents or water-miscible fuels such as alcohols, acetone, ethers, etc.

In addition to its use in aspirating foam equipment, First Strike™ Low-Temp AFFF can be dispensed effectively through non-aspirating equipment including water fog nozzles and standard sprinklers. Additionally, it is also compatible with dry chemical fire fighting agents and may be applied to fires simultaneously.

FEATURES

Effective: Rapid extinguishment reduces the chances of dangerous incidents and reduces the risk to property and equipment. First Strike™ Low-Temp AFFF Solution also reduces reflash and burn back, which are major causes of injuries. Its securing action of minimizes the fire hazard during cleanup of flammable liquid spills.

Reliable: First Strike™ Low-Temp AFFF Solution can be stored virtually indefinitely in approved equipment/systems. NFPA 11 recommends annual inspection of all foam systems.

Economical: First Strike™ Low-Temp AFFF Solution offers faster extinguishment than protein-based foams, so less agent is required in training and actual fire emergencies. Its wide range of applications reduces or eliminates the need to inventory other special type agents.

Storage and Design: First Strike™ Low-Temp AFFF Solution provides maximum economies in storage space and design of fixed systems.

LOW-TEMPERATURE PROTECTION

First Strike™ Low-Temp AFFF Solution is specially formulated to provide freeze protection at temperatures as low as -22°F (-30°C).

TYPICAL PHYSICAL PROPERTIES

Appearance: Clear, Off-White Liquid
Specific Gravity @ 77°F (25°C): 1.020 ± 0.025
pH: 7.0 - 8.5
Viscosity @ 77°F (25°C): 14.0 ± 2 cP
Minimum Use Temperature: -22°F (-29°C)
Storage Temperature: -22° - 120°F (-30° - 49°C)
Freeze Point: < -22°F (-30°C)
Shelf Life: When properly stored in the original (or approved) sealed container and stored within the recommended temperature range, a shelf life in excess of 25 years can be expected.

ENVIRONMENTAL INFORMATION

First Strike™ Low-Temp AFFF Solution undergoes a program of ongoing testing to assess the impact on the natural environment. U.S. Foam products are low in toxicity to tested aquatic organisms.

Aquatic life is not adversely affected when First Strike™ Low-Temp AFFF Solution is used and disposed of properly. U.S. Foam products can be successfully treated in biological waste water treatment systems.

This product does not contain any components with reportable quantities under SARA Title III Section 313.

STORAGE

First Strike™ Low-Temp AFFF Solution may be stored in its shipping container without change to its original physical or chemical characteristics. It does not show significant sedimentation or precipitation in storage or after temperature cycling. Freeze/thaw cycling has no effect on performance, and the solution performs satisfactorily in temperatures above -22°F.

Freeze/thaw cycling may cause slight stratification which may be overcome with moderate agitation.

ORDERING INFORMATION

First Strike™ Low-Temp AFFF Solution is available in pails, drums or totes.

| Part No. | Container | Shipping Weight |
|----------|--------------------------|--------------------|
| 1440.005 | 5 gallon (19 L) pail | 46 lbs (21 kg) |
| 1440.055 | 55 gallon (208 L) drum | 491 lbs (223 kg) |
| 1440.275 | 275 gallon (1041 L) tote | 2490 lbs (1130 kg) |

The data contained herein is provided for general informational purposes only. US Foam Technologies, Inc. reserves the right to change any portion of this technical data sheet without notice.