



Solv Kleen

SOLV KLEEN is a highly concentrated blend of biodegradable wetting agents, emulsifiers, and oil release agents. **SOLV KLEEN** is completely biodegradable and is environmentally safe to use. **SOLV KLEEN** is designed to mitigate and disperse hydrocarbon fuel spills on pavement and roadways as well as water.

SOLV KLEEN is biodegradable, non-toxic, non-corrosive, nor harmful to the environment.

Recommended Application Rates

- ✓ *Fuel Spills on Roadway or Pavement:* Proportion SOLV KLEEN @ 2% in water and apply to spill area. Agitate and flush with generous amounts of water.
- ✓ *Spills on Water:* Spray undiluted SOLV KLEEN directly to the spill agitate.
- ✓ *Rail Cars:* Use 1-2% ration through Roto Jet or Butterworth type equipment for degassing and clearing.
- ✓ *Storage Tanks:* Charge vessel or tank with a 2% solution of SOLV KLEEN in water and circulate until process is complete.

Typical Properties

Proportioning Ratio	2.0% - 5.0%
Specific Gravity	1.056
pH	10.0-10.5
Viscosity	17
Shipping Specifications	5 gal pails (19 Liters) 55 gal drums (209 Liters)
Storage Temperature	32-122 Degrees Fahrenheit
Shelf Life	When properly maintained in the original (or approved) container and stored within the recommended range, a shelf life in excess of 25 years can be expected. If freezing does occur, thawing will render the product completely serviceable.

Environmental Impact:

This product does not contain any reportable agents under SARA TITLE III, Section 313

Listings:

This product meets NFPA 11 A requirements

For question or Technical Information, contact your U.S. Foam representative
Phone: 800-595-3626(FOAM) • Fax: 877-873-6261
800 EAST COTTON ST • LONGVIEW, TX 75602 • WWW.USFOAM.COM